



TABLE A

| SPEED (MPH) | TAPER LENGTH (FT) | | CONE SPACING ALONG TAPER (FT) |
|----------------|----------------------|-------|-------------------------------------|
| | OFFSET | WIDTH | |
| | 10' | 12' | |
| 25 | 100 | 120 | 25 |
| 30 | 150 | 180 | 30 |
| 35 | 200 | 240 | 35 |
| 40 | 270 | 320 | 40 |
| 45 | 450 | 540 | 45 |

NOTE:

1. DISTANCE BETWEEN SIGNS SHALL BE 100' FOR RESIDENTIAL STREETS (25 MPH), AND 200' FOR ARTERIAL ROADWAYS
2. RETROREFLECTORIZED SIGNS AND FLASHING BEACON SHALL BE INSTALLED AT EACH SIGN FOR NIGHT-TIME USE.
3. DISTANCES MAY VARY AS APPROVED BY THE ENGINEER.
4. FLAGGERS REQUIRED TO CONTROL TRAFFIC WHENEVER THE CONTRACTOR MUST INTERRUPT TRAFFIC FLOW TO ACCESS THE WORK SITE WITH MATERIALS OR EQUIPMENT.

LEGEND:

- ⊗ CONE OR CHANNELIZING DEVICE
(SEE STD 7-13)

